

INSTRUCTIONS FOR USE

A-dec 371 and 372 Dental Light

Copyright

© 2013 A-dec Inc. All rights reserved.

A-dec Inc. makes no warranty of any kind with regard to this material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. A-dec Inc. shall not be held liable for any errors contained herein or any consequential or other damages concerning the furnishing, performance or use of this material. The information in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. A-dec Inc. does not warrant that this document is error-free.

No part of this document may be copied, reproduced, altered, or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, without prior written permission from A-dec Inc.

Trademarks and Additional Intellectual Property Rights

A-dec, the A-dec logo, A-dec 500, A-dec 300, Cascade, Cascade Master Series, Century Plus, Continental, Decade, ICX, ICV, Performer, Preference, Preference Collection, Preference ICC, and Radius are trademarks of A-dec Inc. and are registered in the United States and other countries. A-dec 400, A-dec 200, Preference Slimline, and reliablecreativesolutions are also trademarks of A-dec Inc. None of the trademarks or trade names in this document may be reproduced, copied, or manipulated in any manner without the express, written approval of the trademark owner.

Certain touchpad symbols are proprietary to A-dec Inc. Any use of these symbols, in whole or in part, without the express written consent of A-dec Inc., is strictly prohibited.


Regulatory Information

The *Regulatory Information and Specifications* document is delivered with A-dec dental device equipment as mandated by agency requirements. If you need this information, please go to the Document Library at www.a-dec.com.

Product Service

Product service is available through your local authorized A-dec dealer. For service information, or to locate an authorized dealer, contact A-dec at 1.800.547.1883 in the USA and Canada or 1.503.538.7478 worldwide, or visit www.a-dec.com.

CONTENTS



1 Introduction.....	3
About Your Dental Light.....	3
2 Basic Operation	5
Power On/Off	5
Light Intensities	5
Auto On/Off Feature	6
Circuit Breaker Locations	6
3 Adjustments and Maintenance	7
Focus Setting	7
Dental Light Positioning.....	7
Rotation Adjustments	8
Bulb Replacement	9
Maintenance Parts	10
Clean / Maintain	10
Barrier Protection	10
4 Appendix: Warranty and Specifications	11
Warranty	11
Specifications.....	12
Operating Specifications	12
Nominal Light Intensity	12

INTRODUCTION



Thank you for choosing A-dec equipment. This guide contains basic operating instructions, adjustments, and maintenance for your A-dec dental light.

About Your Dental Light


The A-dec 371/372 dental light is designed to make your job easier. Balanced light gives a clear view of tooth surfaces, the precision-balanced arm allows for smooth positioning, and touchpad controls make operation convenient for you and your team.

Figure 1. A-dec 371/372 Dental Light



WARNING Take appropriate precautions when operating and maintaining the dental light. Avoid contact with components that may become hot when the light is on. To avoid burns, touch only the light handles and switches during operation. Always turn off the light and allow it to cool completely before maintenance or service.

Figure 2. A-dec 371/372 Dental Light Features




Item	Description
A	Flexarm
B	Bulb Cap Assembly
C	Light Shield
D	Light Handle
E	On/Off Switch
F	Pivot Housing

BASIC OPERATION

Power On/Off

To turn the light on, press the dental light button on the touchpad (see Figure 3). To turn the light off, press and hold the light button. You can also use the manual on/off switch on the pivot housing (see Figure 2 on page 4).

Figure 3. Dental Light Touchpad Controls



A) Dental Light Button	D) Treatment Position Button(s)
B) Program Button	E) Entry/Exit Button
C) X-Ray/Rinse Position Button	F) Dental Light Indicator (LED)

Note: Touchpad symbols are proprietary to A-dec Inc.

Light Intensities

The A-dec 371/372 dental light features two light intensities: high and composite*. After turning the light on, press the dental light button to toggle between the two intensity settings. On standard touchpads, an LED indicator illuminates when the dental light is in the high intensity setting. When the dental light is in the composite setting, the LED indicator flashes.

** High intensity is the only available setting on systems without a touchpad.*

Auto On/Off Feature

The dental light includes a convenient auto on/off feature. Press any button that moves the chair into a treatment position (see Figure 3 on page 5), and the dental light turns on when the chair reaches that position. Press the entry/exit or x-ray/rinse buttons and the dental light automatically turns off.

To activate/deactivate the auto on/off feature:

- Press and hold the program and dental light buttons simultaneously for three seconds. One beep confirms the auto on/off is off.
- Press and hold the program and dental light buttons simultaneously for three seconds. Three beeps confirm that the auto on/off is on.






NOTE For further instructions on programming the touchpad, please refer to the *A-dec 300 Systems Instructions For Use* (p/n 86.0092.00).

Circuit Breaker Locations

Under abnormal conditions, the circuit breaker interrupts the flow of electricity. If the circuit breaker should trip, reset it by pushing the circuit breaker button on the power supply. For the specific button location, see Figure 4.

Figure 4. Circuit Breaker Locations

Chair Model	Power Supply Location	Circuit Breaker Location
A-dec 311	Chair motor pump area	
A-dec 511	Chair motor pump area	
Cascade, [®] Decade, [®] Performer, [®] and non-A-dec chairs	Utility floor box	

ADJUSTMENTS AND MAINTENANCE



Focus Setting



WARNING Always turn off the dental light and allow it to cool completely before maintenance or service.

The A-dec 371/372 dental light is factory set for optimum illumination between 12 - 27 inches (300 - 700 mm) from the oral cavity. This setting is fixed and cannot be adjusted.

Dental Light Positioning

Properly adjusted, your dental light should rotate and pivot to provide smooth positioning. If the light head is difficult to position, moves too easily, or tends to slip out of position, you can adjust the horizontal and vertical tension (see Figure 6 and Figure 7 on page 8).

Figure 5. Light Head Rotation



Rotation Adjustments

To adjust the horizontal rotation, use a 5/32" hex key to tighten or loosen the horizontal tension screw (see Figure 6).

To adjust the vertical rotation, use a 3/16" hex key to tighten or loosen the vertical tension screw (see Figure 7).

Figure 6. Horizontal Rotation Adjustment





Figure 7. Vertical Rotation Adjustment



Bulb Replacement


A spare bulb is included with your dental light. Follow these steps when replacing the bulb:



WARNING To avoid burning your fingers, allow the light shield to cool before removing. Never operate the dental light with the light shield removed. The light shield contains UV blocking additives. The light shield is also your protection in the unlikely event that the bulb shatters.

1. Turn OFF the light and allow it to cool.
2. Gently pull out on the light shield tabs, then pull the edges of the shield toward you (see Figure 8). Set the light shield aside.

Figure 8. Remove Light Shield



3. Remove the bulb cap by rotating it counterclockwise. Set the bulb cap aside.



CAUTION Take care when handling the bulb. The bulb base is fragile and can break under excessive pressure.


4. Using a gauze pad or cloth to protect your fingers, carefully pull the old bulb from its socket. Discard the bulb.



CAUTION Do not remove the outer wrapper when handling the new bulb. Finger oils can affect light performance and severely limit bulb life. If you should inadvertently touch the bulb, gently clean it with cotton dampened with isopropyl or ethyl alcohol.

5. Holding the new bulb in its outer wrapper with the pins away from you, carefully insert the bulb pins into the socket (see Figure 9). A small section of each pin is still visible when the bulb is fully seated.

Figure 9. Insert New Bulb



- Remove and discard the outer wrapper. Then reinstall the bulb cap and light shield.



CAUTION Do not attempt to install the light shield if it has a broken tab. Contact your authorized A-dec dealer for a replacement shield and install before operating the light.

- Verify the operation of the light by turning it on and operating it at each intensity setting.

Maintenance Parts

Description	Part Number	
Bulb	041.709.00	
Bulb Cap	28.1635.00	
Shield	26.1634.00	

Clean / Maintain

Barrier Protection



CAUTION If you use barriers, always replace the barrier film after each patient.

A-dec recommends barrier protection for all applicable touch and transfer surfaces. Touch surfaces are areas that come into contact with hands and become potential cross-contamination points during dental procedures. Transfer surfaces are areas that come into contact with instruments and other inanimate objects.

In the USA, barriers must be produced under the Current Good Manufacturing Practice (CGMP) as specified by the U.S. Food and Drug Administration (US FDA). For regions outside the USA, refer to the medical device regulations specific to your location.



IMPORTANT For recommendations on cleaning and chemical disinfection of touch and transfer surfaces (where barrier protection is not applicable or when barriers are compromised), please see the *A-dec Equipment Asepsis Guide* (p/n 85.0696.00) included with your equipment.

APPENDIX: WARRANTY AND SPECIFICATIONS



Warranty

A-dec warrants all products against defects in materials or workmanship for one year from time of delivery. A-dec's sole obligation under the warranty is to provide parts for the repair, or at its option, to provide the replacement product (excluding labor). The buyer shall have no other remedy. All special, incidental, and coincidental damages are excluded.

Written notice of breach of warranty must be given to A-dec within the warranty period. The warranty does not cover damage resulting from improper installation or maintenance, accident or misuse. The warranty does not cover damage resulting from the use of cleaning, disinfecting or sterilization chemicals and processes. The warranty also does not cover light bulbs. Failure to follow instructions provided in the *A-dec Instructions For Use* (operation and maintenance instructions) may void the warranty.

A-dec warrants A-dec dental chair cylinders, both lift and tilt for ten years from the date of purchase of the chair or the cylinder. This warranty is retroactive to A-dec chair cylinders already in the field. The warranty covers chair cylinders A-dec finds to have manufacturing irregularities. Stool cylinders are covered under A-dec's one-year warranty.

No other warranties as to merchantability or otherwise are made. For service information, contact your local authorized A-dec dealer. Check with local codes and ADA (Americans with Disabilities Act) requirements for installation of this product.



CAUTION Federal law restricts this device to sale by or on the order of a dentist, physician, or any other practitioner licensed by law of the state in which he or she practices to use or order the use of this device.

Specifications

Operating Specifications

- Operating voltage: 100, 120, or 240V
- Focal range: Adjustable; 18 - 31 inches (457 - 787 mm)
- Bulb: Quartz Xenon Halogen, single-end prongs
- Lamp rating: 17V/ 95W
- Color temperature: 5000 Kelvin
- Light pattern: 3.3" x 6.3" at 27.6" (84 mm x 160 mm at 701 mm)

Nominal Light Intensity

- Composite: 8,000 lux (743 fc)
- Medium: 20,000 lux (1858 fc)
- High: 24,000 lux (2230 fc)
- Heat output: 325 BTU/hour



NOTE Specifications are subject to change without notice.



A-dec Headquarters

2601 Crestview Drive
Newberg, OR 97132 USA
Tel: 1.800.547.1883 Within USA/Canada
Tel: 1.503.538.7478 Outside USA/Canada
Fax: 1.503.538.0276
www.a-dec.com

International Distribution Centers

A-dec United Kingdom

Authorized EU Representative
Austin House, 11 Liberty Way
Nuneaton, Warwickshire CV11 6RZ
England
Tel: 0800 ADECUK (233285) Within UK
Tel: +44 (0) 24 7635 0901 Outside UK
www.a-dec.co.uk

A-dec Australia

Unit 8
5-9 Ricketty Street
Mascot, NSW 2020
Australia
Tel: 1.800.225.010 Within Australia
Tel: +61 (0)2 8332 4000 Outside Australia
www.a-dec.com.au



86.0220.00 Rev E
Copyright 2013 A-dec Inc.
All rights reserved.